



US006519554B1

(12) **United States Patent**  
Gieseke et al.

(10) Patent No.: **US 6,519,554 B1**  
(45) Date of Patent: **Feb. 11, 2003**

(54) **COMPUTER IMPLEMENTED SYSTEM AND METHOD FOR EVALUATING GAS GENERATOR LAUNCHERS**

5,721,680 A • 2/1998 Van Cleve et al. .... 701/3  
5,918,307 A • 6/1999 Cipolla ..... 89/1.81  
6,146,114 A • 11/2000 Nardacci et al. .... 417/437

#### OTHER PUBLICATIONS

(75) Inventors: Thomas J. Gieseke, Newport, RI (US);  
Michael W. Williams, Middletown, RI (US); Jeffrey L. Cipolla, Newport, RI (US)

Theunissen et al., D.J. Effects of Environment and Aging Upon Missile Reliability, Reliability and Maintainability Symposium, 1998, pp. 314-320.\*

(73) Assignee: The United States of America as represented by the Secretary of the Navy, Washington, DC (US)

Chapuis et al., Determination and Influence of the Main Parameters for the Launch and Recovery of an Unmanned Underwater Vehicle from a Submarine, Proceedings of the 1996 Symposium on Autonomous Underwater Vehicle Technology, AUV '96, pp. 276-282.\*

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

\* cited by examiner

(21) Appl. No.: 09/313,314

Primary Examiner—Russell Frejd

(22) Filed: May 17, 1999

(74) Attorney, Agent, or Firm—Michael J. McGowan; James M. Kasischke; Michael F. Oglo

(51) Int. Cl.<sup>7</sup> ..... G06F 7/48  
(52) U.S. Cl. .... 703/6; 703/2  
(58) Field of Search ..... 703/2, 6; 89/1.81,  
89/1.807, 1.809, 1.11; 114/238, 20.1, 20.2;  
244/3.21, 3.22; 42/1.14, 1.41; 235/401;  
102/456; 92/90; 701/3; 417/437

#### (57) ABSTRACT

A computer-implemented system and method for evaluating gas generator launchers is provided. The method includes fixing the system geometry and establishing initial conditions of the launcher to be evaluated. The initial conditions include a mass, composition and geometry of the fuel included in the gas generant, geometries of the system components, initial pressures and temperatures and the mass and geometry of the device to be launched. A gas generator internal ballistics burn rate is modeled and an amount of mass and energy added to the combustion chamber as the fuel is consumed is calculated. Then, using conservation of mass and energy principles, an energy flux rate is modeled, beginning with the fuel and ending with the work performed on the device in order to propel it from the launcher. The modeling method is performed using a computer-based gas generator launcher simulation system, which includes a means for inputting gas generator launcher geometries and initial conditions, a launcher simulator program in computer memory for resolving gas and device dynamic equations to integrate a solution from said initial conditions to the end of a launch cycle, and a display means for displaying the integrated solution.

#### (56) References Cited

##### U.S. PATENT DOCUMENTS

3,137,203 A	• 6/1964	Brown	.....	89/1.81
3,279,319 A	• 10/1966	Semonian et al.	..	89/1.81
3,516,380 A	• 6/1970	Johnston	.....	114/238
3,692,258 A	• 9/1972	Parilla	.....	244/3.21
3,806,064 A	• 4/1974	Parilla	.....	244/3.22
3,807,274 A	• 4/1974	Cohen	.....	89/1.81
4,077,147 A	• 3/1978	Donnard et al.	..	42/1.14
4,246,472 A	• 1/1981	Sun et al.	.....	235/401
4,357,888 A	• 11/1982	Phillips et al.	....	114/20.1
4,372,239 A	• 2/1983	Hagelberg et al.	.....	114/20.2
4,584,925 A	• 4/1986	Culotta et al.	....	89/1.807
4,742,775 A	• 5/1988	Harris	.....	102/456
4,821,441 A	• 4/1989	Castro, Jr. et al.	..	42/1.41
5,230,276 A	• 7/1993	Collett	.....	92/90
5,425,301 A	• 6/1995	Kriebel	.....	89/1.809
5,639,982 A	• 6/1997	Cipolla	.....	89/1.11

10 Claims, 6 Drawing Sheets

